



EM500-UDL

Ultrasonic Distance/Level Sensor



Introduction

EM500-UDL ultrasonic level sensor is a long range wireless sensor compatible with standard LoRaWAN protocol. Combining with the advanced LoRa technology and 19000mAh battery make it a low power consumption product with years-long use life. It can measure the distance to a wide range of objects by using ultrasonic sound waves and provides highly accurate continuous level measurement of most liquid material.

Features

- Up to 11km communication range
- Standard LoRaWAN protocol
- Easy Configuration via NFC
- Ursalink Cloud and third-party platform compliant
- Low power consumption with 19000 mAh replaceable battery
- 1-Year Warranty Included

Applications

- ✓ Water level monitoring in running water
- √ Flood monitoring
- √ Waste water management, sewer system monitoring
- ✓ Level/depth monitoring in water tanks
- ✓ Smart agriculture: fill level monitoring in grain, fertilizer or pellets silos
- ✓ Snow level monitoring

Specifications

LoRaWAN CONTROL OF THE CONTROL OF TH		
Frequency	EU433/CN470/IN865/EU868/RU864/US915/AU915/KR920/AS923	
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)	
Sensitivity	-147dBm @300bps	
Mode	OTAA/ABP Class A	
Antenna	Integrated ceramic antenna	
Distance Measurement		
Dango	0.3-5m/0.5-10m	
Range	(Customizable for snow level detection)	
Resolution	1 mm	
Accuracy	±1%	
Physical Characteristics		
Power Supply	19000 mAh Li-SOCL2 battery	
Battery Life	6 years (10 min interval, SF12)	
	>10 years (10 min interval, SF7)	
Operating Temperature	-20°C to +70°C	
Ingress Protection	IP66 (IP67 as required)	
Dimension	156.1 × 71 × 69.5 mm	

Mounting	Pole, wall, DIN Rail	
Operation		
Power On & Off	NFC, power button (Internal)	
Configuration	Mobile APP or PC software via NFC or USB Type-C	

Order Information

Model	Measuring Range
EM500-UDL-W050	0.3-5m
EM500-UDL-W100	0.5-10m



4/F, No. 63-2 Wanghai Road, 2nd Software Park Xiamen 361008, China

Phone: +86-592-5023060 Fax: +86-592-5023065
Website: www.ursalink.com Email: contact@ursalink.com

